



HYDRO

Standard Features

Frame:

All Aluminum Tube Construction
Aluminum 2" x 3" Tube Main Frame
Aluminum 1.5" x 3" Tube Crossmembers (24" O/C)
Aluminum Tube Wall Post (16" O/C)
Aluminum Tube Roof Bows (16" O/C)

Axles/Wheels:

Single 3500# Dexter Torsion Idler Axle (Tandem Axle Option Available)
ST145/R12E 12" E Rated Wheels With Steel Rims

Electrical:

LED Taillights
Bullet Marker Lights (2/Side)
4-Way Flat Plug

Interior:

3/4" Drymax Flooring
12" Drymax Kickplate
Full Length Slide Track With Ski Bar Tie Downs (2)
Interior Dome Light With Switch

Exterior:

.030 Screwless Exterior
1 Piece Aluminum Roof
ATP Front Radius Stoneguard
Flo-Thru Vents
All Aluminum Door Hardware
Black Insert Molding Trim
19" x 58" Front Access Door With 2 RV Latches
26" x 58" Man Door With RV Latch (No Barlock)
Aluminum Entry Step
Wishbone Tongue With Straight 2" Coupler
2000# Front Jack

Safety/Warranty:

DOT/CSA Safety Equipment
3 Year Structural Warranty
1 Year Limited Warranty